


LEAD FINISH: SOLDER	
BUSHING FINISH: SILVER	
CAPACITANCE	4000 pF MIN.
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP MAX.
WORKING VOLTAGE	85°C 500 VDC MAX. 125°C 300 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
10	15
30	30
100	65
300	70
1 GHz	70


SCHMATIC



MARKING:

PART: S001
BAG:

1221-001
DATE CODE
LOT NO.
QTY./BAG (100 MAX.)

	6	5	4	3	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	 FAIRVIEW PENNSYLVANIA	
	CN #18933	CN. 211000	CN. 210426	CN. 184995 REDRAWN	CHANGE NOTICE	Fractions ± 1/32	Dwn. KAUFFMAN	Description Pi
						Dec. .xx±	Date 3-14-16	RESIN SEAL FILTER
						Dec. .xxx±.015	Engr.	1221-001
						Angles ±0° 30'	Scale NONE	
						CODE IDENT. NO. OLSP2		